

# PERMABOND®

## Anti-Seize



Ref. #: 041509PBAnti-seize

### FEATURES and BENEFITS:

- Protects Against Rust & Corrosion
- Reduces Friction-Provides Constant Torque/Tension
- Speeds Assembly or Disassembly
- Prevents Seizing, Galling and Cold Welding
- Retards Galvanic Action Between Dissimilar Metals
- Resists Salt water Corrosion
- Compatible with all Types of Metals
- Non-Hardening and Non-Dripping

### DESCRIPTION

PERMABOND **Anti-Seize** is a superior grade assembly compound and high pressure lubricant. This high quality aluminum, copper and graphite based anti-seize formula has unique particle shapes suspended in special carriers. It will protect metal parts under extreme heat, pressure and contaminating conditions to 2000°F (1095°C).

**Anti-Seize** is designed with ultra fine metallic and graphite particles enhancing a longer lasting protective film, resisting washout, burn-off and corrosion.

### PHYSICAL PROPERTIES:

Consistency	Homogeneous Paste
Appearance	Silver Grey
Shelf life, months	12
Corrosivity	Non-corrosive to ferrous metals
Operating Temperature	-300°F (-184°C) to 2000°F (982°C)

Non-Warranty: The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers before using any product in full-scale production make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. THE PRODUCTS DISCLOSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED.

No representative of ours has any authority to waive or change the foregoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the non-existence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of this patent. We also expect purchasers to use our products in accordance with the guiding principles of the Chemical Manufacturers Association's Responsible Care® program.

PERMABOND  
14 Robinson Street, Pottstown, PA 19464

Application Assistance: 1-800-640-7599 Customer Service: 1-800-714-0170  
Fax No.: 1-800-334-3219

<http://www.permabond.com>

## **STORAGE & HANDLING**

PermaBond **ANTI-SEIZE** should be stored in a cool, dry place in the unopened container at a temperature between 5°C and 25°C (41°F and 80°F). Under these conditions the product has a shelf life of 12 months.

**Please refer to the MSDS for more information on the handling of this material.**

**FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN**