



For immediate release

March 31, 2005

Editorial Contact:

Laurie Gibbons

Phone 860-379-9172

laurie.gibbons@permabond.com

Technical Contact:

Manny Dias

Phone 732-868-1372

manny.dias@permabond.com

PERMABOND LAUNCHES EPOXY ADHESIVE RANGE

SOMERSET, NJ – Permabond® Engineering Adhesives is pleased to announce the launch of a brand new range of high-performance epoxy adhesives. Epoxies are ideal for high-strength bonding of a wide variety of materials and have excellent resistance to harsh environmental conditions, chemicals and water.

Permabond's new products have been designed for ease of use - adhesive is available in easy-to-dispense cartridges with mixing nozzles. They have a 1:1 mix ratio (resin and hardener) and cure at room temperature. Several of the new products have rapid cure speeds, offering the user benefits in terms of reduced clamping times and increased production rates. Other products in the new range include a clear, non-yellowing epoxy and a flexible grade with high peel-strength, allowing the user greater freedom of joint design while still maintaining performance. The new adhesives are suitable for bonding, sealing, encapsulating and repairing plastics, metal, composites, ceramics, and wood.

Permabond is a global manufacturer of engineering and industrial adhesives and sealants for manufacturing, assembly, repair and maintenance. Permabond's commitment to quality assures reliable solutions for the most demanding applications. Permabond offers a complete line of adhesive technologies, technical service support and custom formulating.

For technical information or for a local distributor, please contact Permabond by mail: 20C World's Fair Drive, Somerset, NJ 08873; phone: 800-640-7599; fax: 800-334-3219 or email: help.americas@permabond.com. You may also visit our website at www.permabond.com.

###