

For immediate release
January 11, 2010

Editorial Contact:

Laurie Gibbons
Phone 860-379-9172
laurie.gibbons@permabond.com

Technical Contact

Manny Dias
Phone 732-868-1372
manny.dias@permabond.com

Permabond Expands its Structural bonding Product line

SOMERSET, NJ –Permabond® Engineering Adhesives introduces Permabond ET538 for structural bonding. ET538 is a two component, room temperature curing epoxy adhesive that has excellent adhesion to a wide variety of surfaces such as ceramic, wood, metal, and many plastic and composite materials. Formulated with a long pot life, it is ideal for large applications and batch production processes. The "non-slump" nature makes it suitable for gap filling and vertical applications. Permabond ET538 forms high strength durable bonds which resist common liquids including gasoline, oil and water.

ET538 is available in a dual cartridge and is dispensed through static mix nozzles to eliminate hand mixing.

Permabond is a global, ISO 9001:2000 certified manufacturer of engineering adhesives and sealants for manufacturing, assembly, repair, and maintenance. Permabond manufactures cyanoacrylates (instant adhesives), anaerobics (for threadlocking, retaining, gasketing and pipe sealing), structural adhesives (one or two component epoxies and toughened acrylic adhesives), and UV - visible curable adhesives. Permabond custom formulates for unique requirements. Permabond products are sold worldwide through authorized distributors.

For information please contact Permabond by mail: 223 Churchill Ave., Somerset, NJ 08873; phone: 732-868-1372 or 800-640-7599; fax: 800-334-3219 or email: info.americas@permabond.com. Visit our NEW website at www.permabond.com.

###

"Our Science . . . Your Success"

Help Line: 800.640.7599 • Customer Service: 800.714.0170 • Fax: 800.334.3219 • Sales Support: 610.323.6952

Headquarters: 223 Churchill Ave, Somerset, NJ 08873 • **Telephone:** 732.868.1372 • **Fax:** 732.868.0267

Warehouse: 14 Robinson Street, Pottstown, PA 19464 • **Telephone:** 610.323.5003 • **Fax:** 610.323.6980

www.permabond.com



