

For immediate release
March 1, 2012

Editorial Contacts:

Laurie Gibbons
Tel. 860-379-9172
laurie.gibbons@permabond.com

Daniela Davidson
Tel. +44 (0)1962 711661
daniela.davidson@permabond.com

Technical Contacts:

Manny Dias
Tel. 732-868-1372
manny.dias@permabond.com

Rebecca Wilmot
Tel. +61 43 033 0009
rebecca.wilmot@permabond.com

Permabond Increased Temperature Resistance of Cyanoacrylate Adhesives

SOMERSET, NJ – Permabond is pleased to announce increased temperature resistance for two popular cyanoacrylate adhesives. Permabond 792 Surface Insensitive Adhesive and 2011 Non Sag Gel Adhesive now withstand up to 250°F (120°C). Previously the upper limit was 180°F (82°C). This technical advancement does not change other properties of the products or affect the MSDS. “We are pleased to be able to offer these improvements to our customers, and, as part of Permabond’s continuous improvement initiative, we will apply this improvement to additional cyanoacrylate adhesives in the coming months” said Manny Dias, Technical Manager.

About Permabond

Permabond develops and manufactures engineering adhesives and sealants for assembly, manufacturing, repair, and maintenance. Permabond offers custom formulating for unique requirements. Products are sold worldwide through authorized distributors. ISO 9001:2008 For information please visit our website at www.permabond.com or contact us • Americas 732-868-1372 info.americas@permabond.com • Asia + 86 21 5773 4913 info.asia@permabond.com • Europe +44(0)1962 711661 info.europe@permabond.com

"Our Science . . . Your Success"

Help Line: 800.640.7599 • Customer Service: 800.714.0170 • Fax: 800.334.3219 • Sales Support: 610.323.6952

Headquarters: 223 Churchill Ave, Somerset, NJ 08873 • **Telephone:** 732.868.1372 • **Fax:** 732.868.0267

Warehouse: 14 Robinson Street, Pottstown, PA 19464 • **Telephone:** 610.323.5003 • **Fax:** 610.323.6980

www.permabond.com

