

For immediate release March 1, 2013

Editorial Contacts: Laurie Gibbons Tel. 860-379-9172 laurie.gibbons@permabond.com

Daniela Davidson Tel. +44 (0)1962 711661 daniela.davidson@permabond.com <u>Technical Contacts:</u> Manny Dias Tel. 732-868-1372 <u>manny.dias@permabond.com</u>

Rebecca Wilmot Tel. +61 43 033 0009 <u>rebecca.wilmot@permabond.com</u>

## New Permabond Epoxy Adhesives for Food Processing Equipment

SOMERSET, NJ – Permabond is pleased to expand its epoxy adhesive line with a new range of two component epoxies formulated with FDA approved ingredients. These toughened epoxies are manufactured in compliance with the FDA CFR 175.105 and 175.300. The excellent shock and impact resistance coupled with environmental and temperature resistance make these epoxies ideal for food processing and food packaging equipment. Typical food contact applications include bonding filter components, bonding and sealing appliances and food handling equipment. They cure at room temperature or can be heated for a faster cure. The range includes various viscosities, gap filling capabilities and working times to suit most applications, and Permabond custom formulates to suit individual manufacturing needs.

## About Permabond

Permabond develops and manufactures engineering adhesives and sealants for assembly, manufacturing, repair, and maintenance. Permabond offers custom formulating for unique requirements. Products are sold worldwide through authorized distributors. ISO 9001:2008 For information please visit our website at <u>www.permabond.com</u> or contact us • Americas 732-868-1372 <u>info.americas@permabond.com</u> • Asia + 86 21 5773 4913 info.asia@permabond.com • Europe +44(0)1962 711661 info.europe@permabond.com

"Our Science . . . Your Success"

Help Line: 800.640.7599 • Customer Service: 800.714.0170 • Fax: 800.334.3219 • Sales Support: 610.323.6952 Headquarters: 223 Churchill Ave, Somerset, NJ 08873 • Telephone: 732.868.1372 • Fax: 732.868.0267 Warehouse: 14 Robinson Street, Pottstown, PA 19464 • Telephone: 610.323.5003 • Fax: 610.323.6980 www.permabond.com