



For immediate release

May 1, 2005

Editorial Contact:

Laurie Gibbons

Phone 860-379-9172

[laurie.gibbons@permabond.com](mailto:laurie.gibbons@permabond.com)

Technical Contact:

Manny Dias

Phone 732-868-1372

[manny.dias@permabond.com](mailto:manny.dias@permabond.com)

### **PERMABOND LAUNCHES STRUCTURAL ACRYLIC ADHESIVE RANGE**

SOMERSET, NJ – Permabond® Engineering Adhesives is delighted to announce the launch of its new range of high-performance structural acrylic adhesives. The new products have been especially developed for use in demanding, high-stress applications where toughness and durability are of paramount importance.

The new adhesives are ideal for bonding plastics, metal, composites, ceramics, wood and glass. They have excellent resistance to impact, shear and peel loads. Adhesives are available as separate adhesive with brush on initiator. No mixing is required. Also available is a no-mix bead-on-bead acrylic adhesive, eliminating the need for mixing nozzles. The adhesives cure to handling strength within minutes and achieve working strength within 30 minutes, offering the user benefits in terms of reduced clamping times and increased production rates. Permabond's chemists have developed the new structural acrylics with health and safety in mind. Products are non-flammable and non-hazardous for transportation, unlike the majority of structural acrylic adhesives on the market.

Permabond is a global manufacturer of engineering and industrial adhesives and sealants for manufacturing, assembly, repair and maintenance. Permabond's commitment to quality assures reliable solutions for the most demanding applications. Permabond offers a complete line of adhesive technologies, technical service support, and custom formulating.

For technical information or for a local distributor, please contact Permabond by mail: 20C World's Fair Drive, Somerset, NJ 08873; phone: 800-640-7599; fax: 800-334-3219 or email: [help.americas@permabond.com](mailto:help.americas@permabond.com). You may also visit our website at [www.permabond.com](http://www.permabond.com).

###